



EN ISO 20345:2022



DIVENTURE  
**MARMOLADA ZIP**  
 70550-00L

**S3S FO \*CI SC LG SR**

**Size:** 36-48  
**Weight:** 810 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Oil industry, Farming and  
 Gardening



## FEATURES

### UPPER

Greased Nubuk Leather Hydro  
 1,8-2,0 mm  
 Reflex insert

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

QRS02 Green

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX recycled insert - PS method

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Cycled® material with additional LG and SC requirements and SR characteristics.

## TECHNOLOGIES


### Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



### Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.





### PU - PU

SOLE 70



### SLIP RESISTANCE

EN ISO 20345:2022

#### BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP $\geq 0.31$	<b>0,39</b>	
BACKWARD FOREPART SLIP $\geq 0.36$	<b>0,42</b>	

#### SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP $\geq 0.19$	<b>0,20</b>	
BACKWARD FOREPART SLIP $\geq 0.22$	<b>0,31</b>	

### Other



D3O materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.

