



EN ISO 20345:2022



DIVENTURE

MARMOLADA ZIP

70550-00L

S3S FO *CI SC LG SR

Size: 36-48

Weight: 810 gr.

Fit: 11

Working Environment:

Building, Wood-metal carpentry,
Oil industry, Farming and
Gardening



FEATURES

UPPER

Greased Nubuk Leather Hydro
1,8-2,0 mm
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX recycled insert - PS method

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made
from recycled Ccycled® material
with additional LG and SC
requirements and SR
characteristics.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use



Protection elements



RESISTANT
TO 3.0 mm.
NAILS

fibercap sxt

Composite toecap with fiberglass.
Resistant to over 200J. Non metal
perforation resistant insert to over
1100 N with a 3.0 mm truncated cone
nail. Protection over the entire sole of
the foot. Flexible and comfortable



Torsional stability



Support made of rigid plastic
material. It supports the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.



PU - PU

SOLE 70

SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,39	
BACKWARD FOREPART SLIP ≥ 0.36	0,42	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20	
BACKWARD FOREPART SLIP ≥ 0.22	0,31	