



EN ISO 20345:2011


 ATLANTIDA
ELDORADO
 80117-00L

S3 *CI HRO HI SRC
Size: 38-48
Weight: 770 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Engineering, Farming and
 Gardening


FEATURES

UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM-HRO

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM rubber,
 resistant to 300° C by contact
 (HRO), to acids and oils. Design
 with self-cleaning outsole, with
 Antislip standard.

TECHNOLOGIES

Removable Insole

climaction fit

 Removable anatomic and ergonomic
 insole. Absorbent and transpiring
 open-cell foam support. Keeps feet
 fresh. Specifically-designed
 thermoforming for exceptional
 comfort.


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

dynamic control
 technology

 Ergonomic rigid structure. It
 accommodates the heel, adjusting the
 foot support and control of the ankle
 in sideways movements. The plastic
 material increases protection of the
 ankle against sharp or pointy objects.


Torsional stability


STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUALMICRO
 DUALMICRO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)



SOLE 80 PU - RUBBER		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19
		0.13

EN ISO 20344:2011