



EN ISO 20344:2011



ATLANTIDA
EXPLORER
80118-05L

S3 *CI HRO HI WR SRC

Size: 38-48
Weight: 700 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Multipurpose



FEATURES

UPPER

Full Grain-Anilina Leather-Hydro
1,8-2,0 mm
Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Low Shoe

SOLE

PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap.
Outsole in VIBRAM rubber,
resistant to 300° C by contact
(HRO), to acids and oils. Design
with self-cleaning outsole, with
Antislip standard.

TECHNOLOGIES


Removable Insole

climaction fit

Removable anatomic and ergonomic
insole. Absorbent and transpiring
open-cell foam support. Keeps feet
fresh. Specifically-designed
thermoforming for exceptional
comfort.



Protection elements



Composite toe cap with fiberglass.
Resistant to over 200J. Non metal
perforation resistant insert to over
1100 N with a 3.0 mm truncated cone
nail. Protection over the entire sole of
the foot. Flexible and comfortable



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.



Other

DUALMICRO

Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



SRC (SRA+SRB)



SOLE 52 - 53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.36
	HEEL (CONTACT ANGLE °) ≥0.28	
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20344:2011