



EN ISO 20345:2011



## ATLANTIDA EXPLORER 80118-05L

**S3 \*CI HRO HI WR SRC**
**Size:** 38-48  
**Weight:** 700 gr.

**Fit:** 11

**Working Environment:**  
 Building, Farming and Gardening,  
 Mountains, Multipurpose


## FEATURES

### UPPER

 Full Grain-Anilina Leather-Hydro  
 1,8-2,0 mm  
 Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Low Shoe

### SOLE

#### PU-RUBBER VIBRAM-HRO

 Sole with anti-wear scaff cap.  
 Outsole in VIBRAM rubber,  
 resistant to 300° C by contact  
 (HRO), to acids and oils. Design  
 with self-cleaning outsole, with  
 Antislip standard.

## TECHNOLOGIES

### Removable Insole

## climaction<sup>337</sup> fit

 Removable anatomic and ergonomic  
 insole. Absorbent and transpiring  
 open-cell foam support. Keeps feet  
 fresh. Specifically-designed  
 thermoforming for exceptional  
 comfort.


### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

**fibercap sxt**

 Composite toecap with fiberglass.  
 Resistant to over 200J. Non metal  
 perforation resistant insert to over  
 1100 N with a 3.0 mm truncated cone  
 nail. Protection over the entire sole of  
 the foot. Flexible and comfortable


### Lateral stability

## dynamic HC control technology

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.


### Torsional stability



## STABIL•ACTIVE

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,  
 ensuring proven anti-static properties  
 of the footwear over time.


### Other

## DUALMICRO DRY WICKO

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)


 SOLE 52 - 53  
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.36
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19
		0.14

EN ISO 20344:2011