



EN ISO 20345:2011



ATLANTIDA  
**SELLA**  
80088-00L

**S3 \*CI HRO HI SRC**

**Size:** 38-48  
**Weight:** 690 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Farming and  
Gardening



## FEATURES

### UPPER

Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Full Grain Leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Low Shoe

### SOLE

#### PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap.  
Outsole in VIBRAM rubber,  
resistant to 300° C by contact  
(HRO), to acids and oils. Design  
with self-cleaning outsole, with  
Antislip standard.

## TECHNOLOGIES

### Removable Insole

**337**  
**climaction fit**

Removable anatomic and ergonomic  
insole. Absorbent and transpiring  
open-cell foam support. Keeps feet  
fresh. Specifically-designed  
thermoforming for exceptional  
comfort.



### Protection elements



RESISTANT  
TO 3.0 mm.  
NAILS

**fibercap sxt**

Composite toecap with fiberglass.  
Resistant to over 200J. Non metal  
perforation resistant insert to over  
1100 N with a 3.0 mm truncated cone  
nail. Protection over the entire sole of  
the foot. Flexible and comfortable



### Lateral stability

**dynamicControl**  
technology

Ergonomic rigid structure. It  
accommodates the heel, adjusting the  
foot support and control of the ankle  
in sideways movements. The plastic  
material increases protection of the  
ankle against sharp or pointy objects.



### Torsional stability



**STABIL ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



### Other



Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



## SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.19 0.13

EN ISO 20344:2011