



EN ISO 20345:2011 

**ATLANTIDA
STELVIO
80087-00L**

S3 *CI HRO HI SRC

Size: 38-48
Weight: 765 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Engineering, Farming and
Gardening



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Full Grain leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Climaction-Fit 337

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail

TYPE
Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO
Sole with anti-wear scaff cap.
Outsole in VIBRAM rubber,
resistant to 300° C by contact
(HRO), to acids and oils. Design
with self-cleaning outsole, with
Antislip standard.

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability
STABIL ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALWICBO
Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)

SOLE 80 PU - RUBBER		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.13

EN ISO 20344:2011