



EN ISO 20345:2011 

ATLANTIDA
STELVIO
80087-01L

S3 *CI HRO HI SRC

Size: 38-48
Weight: 765 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Engineering, Farming and
 Gardening



FEATURES

UPPER
 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Full Grain Leather Hydro

LINING
 3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO


INSOLE
 Climaction-Fit 337

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 Textile resistant to 3.0 mm nail

TYPE
 Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO
 Sole with anti-wear scaff cap.
 Outsole in VIBRAM rubber,
 resistant to 300° C by contact
 (HRO), to acids and oils. Design
 with self-cleaning outsole, with
 Antislip standard.



SRC (SRA+SRB)

		SOLE 80 PU - RUBBER	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.43	0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19	0.13

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO DUALWICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.