



EN ISO 20345:2011


 ATLANTIDA  
**STELVIO**  
 80087-01L

**S3 \*CI HRO HI SRC**
**Size:** 38-48  
**Weight:** 765 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Engineering, Farming and  
 Gardening


## FEATURES

### UPPER

 Greased Nubuk Dakar Leather  
 Hydro 1,8-2,0 mm  
 Full Grain Leather Hydro

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU-RUBBER VIBRAM-HRO

 Sole with anti-wear scaff cap.  
 Outsole in VIBRAM rubber,  
 resistant to 300° C by contact  
 (HRO), to acids and oils. Design  
 with self-cleaning outsole, with  
 Antislip standard.

## TECHNOLOGIES

### Removable Insole

**337**  
**climaction fit**

 Removable anatomic and ergonomic  
 insole. Absorbent and transpiring  
 open-cell foam support. Keeps feet  
 fresh. Specifically-designed  
 thermoforming for exceptional  
 comfort.


### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

**fibercap sxt**

 Composite toecap with fiberglass.  
 Resistant to over 200J. Non metal  
 perforation resistant insert to over  
 1100 N with a 3.0 mm truncated cone  
 nail. Protection over the entire sole of  
 the foot. Flexible and comfortable


### Lateral stability

**dynamicControl**  
 technology

 Ergonomic rigid structure. It  
 accommodates the heel, adjusting the  
 foot support and control of the ankle  
 in sideways movements. The plastic  
 material increases protection of the  
 ankle against sharp or pointy objects.


### Torsional stability

**STABIL•ACTIVE**

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,  
 ensuring proven anti-static properties  
 of the footwear over time.


### Other

**DUALMICRO**  
**DUALWICKO**

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)



SOLE 80 PU - RUBBER		
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.43</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.19</b>
		<b>0.13</b>

EN ISO 20344:2011