



EN ISO 20345:2011



ATLANTIDA

TERRANOVA
80128-01L
S3 HRO HI CI SRC
Size: 38-48

Weight: 860 gr.

Fit: 11

Working Environment:

Cold places, Mountains, Farming and Gardening, Wood-metal carpentry



FEATURES

UPPER

Full Grain leather Hydro 1,8-2,0 mm

Full Grain leather Hydro

Drummed leather Hydro 1,8-2,0 mm

LINING

GenuineWool Polar

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

SOLE

PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap.

Outsole in VIBRAM rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with Antislip standard.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements



RESISTANT TO 3.0 mm. NAILS

 fibercap **sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic HC control
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability


STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)


 SOLE 80
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.43
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.13

EN ISO 20344:2011