




**EN ISO 20345:2011** 

**ATLANTIDA  
TURTLE  
80196-00L**

**S3 HRO HI \*CI M SRC**

**Size:** 38-48  
**Weight:** 800 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Components and  
Automotive



**FEATURES**

**UPPER**  
Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Soft Full Grain Leather Hydro  
nubuk-look leather 1,4-1,6 mm  
Reflex insert

**LINING**  
3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO


**INSOLE**  
Climaction-Fit 337

**TOE CAP**  
Fiber cap SXT

**RESISTANCE TO PERFORATION**  
Textile resistant to 3.0 mm nail

**TYPE**  
Ankle boot

**SOLE**  
**PU-RUBBER VIBRAM-HRO**  
Sole with anti-wear scaff cap.  
Outsole in VIBRAM rubber,  
resistant to 300° C by contact  
(HRO), to acids and oils. Design  
with self-cleaning outsole, with  
Antislip standard.



**SRC (SRA+SRB)**

		SOLE 80 <b>PU - RUBBER</b>
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.43</b> <b>0.35</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.19</b> <b>0.13</b>

EN ISO 20344:2011

**TECHNOLOGIES**

**Removable Insole** **337**  
**climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



**Protection elements**

**RESISTANT TO 3.0 mm NAILS** **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**

**dynamic control technology**

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



**Torsional stability**

**METATARSAL PROTECT**

Rigid anatomical protection, resistant up to 100 Joules, to protect the metatarsus against falling sheets of metal or similar. For foundries, heavy metal work, glass factories and anywhere sheet metals are handled.



**Electrical features**

**WED**  
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**

**DUALMICRO DUALWICKBO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.