



EN ISO 20345:2011


ATLANTIDA
TURTLE
80196-00L
S3 HRO HI *CI M SRC
Size: 38-48
Weight: 800 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Engineering, Components and
 Automotive


FEATURES

UPPER

Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Soft Full Grain Leather Hydro
 nubuk-look leather 1,4-1,6 mm
 Reflex insert

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU-RUBBER VIBRAM-HRO

Sole with anti-wear scaff cap.
 Outsole in VIBRAM rubber,
 resistant to 300° C by contact
 (HRO), to acids and oils. Design
 with self-cleaning outsole, with
 Antislip standard.

TECHNOLOGIES

Removable Insole

337
climaction fit

Removable anatomic and ergonomic
 insole. Absorbent and transpiring
 open-cell foam support. Keeps feet
 fresh. Specifically-designed
 thermoforming for exceptional
 comfort.



Protection elements



RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable



Lateral stability

dynamicControl
 technology

Ergonomic rigid structure. It
 accommodates the heel, adjusting the
 foot support and control of the ankle
 in sideways movements. The plastic
 material increases protection of the
 ankle against sharp or pointy objects.



Torsional stability

METATARSAL
PROTECT

Rigid anatomical protection, resistant
 up to 100 Joules, to protect the
 metatarsus against falling sheets of
 metal or similar. For foundries, heavy
 metal work, glass factories and
 anywhere sheet metals are handled.




Electrical features

WED

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.



Other

DUALMICRO
DRY WICKO

Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.



SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.43
	HEEL (CONTACT ANGLE °°) ≥0.28	0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.19
	HEEL (CONTACT ANGLE °°) ≥0.13	0.13

EN ISO 20344:2011