




EN ISO 20344:2011 

ATLANTIDA
TURTLE
80196-00L

S3 HRO HI *CI M SRC

Size: 38-48
Weight: 800 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Engineering, Components and
Automotive



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Soft Full Grain Leather Hydro
nubuk-look leather 1,4-1,6 mm
Reflex insert

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO


INSOLE
Climaction-Fit 337

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO
Sole with anti-wear scaff cap.
Outsole in VIBRAM rubber,
resistant to 300° C by contact
(HRO), to acids and oils. Design
with self-cleaning outsole, with
Antislip standard.



SRC (SRA+SRB)

		SOLE 80 PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.13

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

KX **RESISTANT TO 3.0 mm NAILS** **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability

METATARSAL PROTECT

Rigid anatomical protection, resistant up to 100 Joules, to protect the metatarsus against falling sheets of metal or similar. For foundries, heavy metal work, glass factories and anywhere sheet metals are handled.



Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO DUALWICKBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.