



EN ISO 20349-2:2017+A1:2020

ATLANTIDA
WELD 2
80523-00L

S3 WG HRO HI *CI SRC

Size: 38-48
Weight: 780 gr.

Fit: 11

Working Environment:
Multipurpose, Wood-metal carpentry, Engineering, Special



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Soft Full Grain Leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO


INSOLE
Climaction-Fit 337

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO
Sole with anti-wear scaff cap. Outsole in VIBRAM rubber, resistant to 300° C by contact (HRO), to acids and oils. Design with self-cleaning outsole, with Antislip standard.



SRC (SRA+SRB)

		SOLE 80 PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE 1°) ≥ 0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE 1°) ≥ 0.13	0.19 0.13

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

KX RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.




Torsional stability
STABIL ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.