



EN ISO 20345:2011


 CRYSTAL  
**ANCONA**  
**86202-00**
**S2 \*CI SRC**
**Size:** 35-39 40-48

**Weight:** 510 gr.

**Fit:** 11

**Working Environment:**  
 Food and Chemical industry,  
 Ho.Re.Ca.


## FEATURES

### UPPER

MicroFiber XPRO 1,8-2,0 mm

### LINING

 Bacteriostatic Teklife 3D  
 Double non-slip layer of  
 microfibre, resistant up to 200,000  
 cycles. Makes the footwear more  
 comfortable, blocking the foot  
 during use.

### INSOLE

Flyfit

### TOE CAP

Fiber cap SXT

### TYPE

Ankle boot

### SOLE

**PU DUAL-DENSITY SRC**

 Double density PU outsole with  
 tread designed mainly for indoor  
 use. Self-cleaning design and  
 highly non-slip grip. SRC Antislip  
 standard.

## TECHNOLOGIES

### Removable Insole


 The upper layer in contact with the  
 foot is made of a highly resistant  
 netting to ensure exceptional  
 absorption of dampness. A self-  
 forming antibacterial foam layer  
 ensures comfort and correct support  
 of the foot.


### Protection elements

**fibercap sxt**

 Composite toecap, reinforced with  
 fiberglass. Structure with a variable  
 thickness for better performances


### Lateral stability

**dynamic HC control**  
*technology*

 Ergonomic rigid internal structure. It  
 houses the heel into the right seat,  
 adjusting the foot support and control  
 of the ankle sideways movements. It  
 keeps the foot tight to the shoe,  
 allowing the perfect fit.


### Torsional stability

**STABIL•ACTIVE**

 Support made of rigid plastic  
 material. It stabilizes the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features




Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,  
 ensuring proven anti-static properties  
 of the footwear over time.


### Other

**DUAL MICRO**  
**DNV WICBO**

 Double non-slip layer of microfibre,  
 resistant up to 200,000 cycles. Makes  
 the footwear more comfortable,  
 blocking the foot during use.


## SRC (SRA+SRB)


 SOLE 86  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.40</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b>
		<b>0.24</b>

EN ISO 20344:2011