



EN ISO 20345:2011


 CRYSTAL
NEW VERONA
86443-00
S2 *CI SRC
Size: 35-39 40-48

Weight: 500 gr.

Fit: 11

Working Environment:
 Food and Chemical industry,
 Ho.Re.Ca.


FEATURES

UPPER

MicroFiber XPRO 1,8-2,0 mm

LINING

 Bacteriostatic Teklife 3D
 Double non-slip layer of
 microfibre, resistant up to 200,000
 cycles. Makes the footwear more
 comfortable, blocking the foot
 during use.

INSOLE

Flyfit

TOE CAP

Fiber cap SXT

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

 Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.

TECHNOLOGIES

Removable Insole


FLYFIT

 The upper layer in contact with the
 foot is made of a highly resistant
 netting to ensure exceptional
 absorption of dampness. A self-
 forming antibacterial foam layer
 ensures comfort and correct support
 of the foot.


Protection elements

fibercap sxt

 Composite toecap, reinforced with
 fiberglass. Structure with a variable
 thickness for better performances


Lateral stability

dynamic HC control
technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability


STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features




Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other

DUAL MICRO
DNV WICBO

 Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.


SRC (SRA+SRB)


 SOLE 86
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.40 0.32
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.24

EN ISO 20344:2011