



EN ISO 20345:2011

 CRYSTAL  
**PADOVA**  
**86207-00**
**SBA E FO SRC**
**Size:** 35-39 40-48

**Weight:** 450 gr.

**Fit:** 11

**Working Environment:**  
 Food and Chemical industry


## FEATURES

### UPPER

MicroFiber XPRO 1,8-2,0 mm

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### TYPE

Clogs

### SOLE

**PU DUAL-DENSITY SRC**

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.



## SRC (SRA+SRB)


 SOLE 86  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.40</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b>

EN ISO 20344:2011

## TECHNOLOGIES

### Removable Insole

**climaction<sup>337</sup> fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements


**Composite Toe Cap**

Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.



### Lateral stability

**dynamic HC control<sup>technology</sup>**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability


**STABIL-ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features


**WED**  
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other


**DUAL MICRO DWTWICBO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.