



EN ISO 20345:2011

CRYSTAL
PADOVA
86207-00

SBA E FO SRC

Size: 35-39 40-48
Weight: 450 gr.

Fit: 11

Working Environment:
Food and Chemical industry



FEATURES

UPPER

MicroFiber XPRO 1,8-2,0 mm

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

TYPE

Clogs

SOLE

PU DUAL-DENSITY SRC

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.



SRC (SRA+SRB)


SOLE 86
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.40
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

climaction³³⁷ fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements



Composite Toe Cap

Toecap made of plastic, incredibly light and resistant to impact of over 200J, very high elastic coefficient, immediately regaining the original shape without entrapping the toes. Perfect thermal isolation. Not detected by metal detector.



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUAL MICRO DWTWICBO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.