



EN ISO 20345:2011



**CRYSTAL** 

# VENEZIA

86203-00

S2 \*CI SRC

Size: 35-39 40-48 Weight: 460 gr.

Fit: 11

## Working Environment:

Food and Chemical industry, Ho.Re.Ca.



# **FEATURES**

#### **UPPER**

MicroFiber XPRO 1,8-2,0 mm

SRC (SRA+SRB)

≥0.32

HEEL (CONTACT ANGLE 7°) ≥0.28

≥0.18

HEEL (CONTACT ANGLE 7°) ≥0.13

SOLE 86 PU - PU

0.40

0.32

0.19

0.24

EN ISO 20344:201

#### LINING

Bacteriostatic Teklife 3D

#### **ANTISLIP LINING DUALMICRO**

#### **INSOLE**

Flyfit

## **TOE CAP**

Fiber cap SXT

## TYPE

Low Shoe

SRA

DETERGENT SOLUTION

SRB

GLYCEROL

## **SOLE**

## **PU DUAL-DENSITY SRC**

CI AVAILABLE

Double density PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

## **TECHNOLOGIES**

#### Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A selfforming antibacterial foam layer ensures comfort and correct support of the foot.

# **Protection elements**



Composite toecap, reinforced with fiberglass. Structure with a variable thickness for better performances



#### Lateral stability

# dynamic H control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

# Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



### **Electrical features**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



