



EN ISO 20345:2022



DIVENTURE

**BRENNERO BOA®**  
 70534-03L

**S3S FO \*CI SC LG SR**
**Size:** 36-48  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**

 Building, Wood-metal carpentry,  
 Oil industry, Farming and  
 Gardening


## FEATURES

### UPPER

 Greased Nubuk Dakar Leather  
 Hydro 1,8-2,0 mm

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

QRS02 Green

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

### TYPE

Ankle boot

### SOLE

**PU DUAL-DENSITY CCYCLED® SR**

 Two-component PU sole made  
 from recycled Ccycled® material  
 with additional LG and SC  
 requirements and SR  
 characteristics.

**Boa® lace length**

M4 - 115cm

## TECHNOLOGIES

### Removable Insole


 Anatomical breathable insole.  
 Resistant fabric with recycled open-  
 cell foam that absorbs shocks and  
 reduces fatigue. Eliminates sweat  
 with its high ability to evaporate it.  
 Continuous comfort for months and  
 months of use


### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

**fibercap sxt**

 Composite toecap with fiberglass.  
 Resistant to over 200J. Recycled non  
 metal perforation resistant insert to  
 over 1100 N with a 3.0 mm truncated  
 cone nail. Protection over the entire  
 sole of the foot. Flexible and  
 comfortable


### Lateral stability

**dynamicControl**  
 technology

 Ergonomic rigid structure. It  
 accommodates the heel, adjusting the  
 foot support and control of the ankle  
 in sideways movements. The plastic  
 material increases protection of the  
 ankle against sharp or pointy objects.


### Torsional stability


**STABIL ACTIVE**

 Support made of rigid plastic  
 material. It supports the heel bone,  
 the instep and tarsal joints, without  
 altering energy absorption. A support  
 for the natural movement of the foot;  
 it provides comfort and greater  
 stability.


### Electrical features


 ESD footwear discharge static  
 electricity and avoid damaging  
 surrounding objects; they are  
 designed in compliance with the  
 following standards: IEC EN  
 61340-5-1:2016 - IEC EN  
 61340-4-3:2018 - IEC EN  
 61340-4-5:2018.

### Other


**FIT TO GO  
 FURTHER™**

 A patented closing system with a multi  
 coated stainless steel cable. The  
 BOA® Fit System delivers micro-  
 adjustable precision fit, engineered to  
 perform in the toughest conditions.


### PU - PU

SOLE 70

### SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,39	
	BACKWARD FOREPART SLIP ≥ 0.36	0,42	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,20	
	BACKWARD FOREPART SLIP ≥ 0.22	0,31	