



EN ISO 20345:2022+A1:2024



DIVENTURE

CRODA BOA®
72568-00L
S7S FO HI HRO *CI CR AN SC LG SR
Size: 36-48
Weight: 850 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Engineering, Special


FEATURES

UPPER

 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot

SOLE

PU-VIBRAM® RECYCLED ECOSTEP
- TRACTION LUG

 PU midsole with scuff cap (SC)
 made with recycled Cycled
 material. VIBRAM rubber outsole
 with Traction Lug technology and
 "Ecostep Pro" compound. SR and
 Ladder Grip standard.

Boa® lace length
 L+1 - 115cm

TECHNOLOGIES

Removable Insole


 Anatomical breathable insole.
 Resistant fabric with recycled open-
 cell foam that absorbs shocks and
 reduces fatigue. Eliminates sweat
 with its high ability to evaporate it.
 Continuous comfort for months and
 months of use


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Recycled non
 metal perforation resistant insert to
 over 1100 N with a 3.0 mm truncated
 cone nail. Protection over the entire
 sole of the foot. Flexible and
 comfortable


Lateral stability


 Ankle Stability Protection means
 safety in movement. Made from high-
 strength TPU, it protects and supports
 the ankle. Promotes healthier posture
 and a more natural gait.


Torsional stability


STABIL ACTIVE

 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


TRACTION LUG

 It is the ideal solution for those
 working on uneven, rocky and
 abrasive terrain. With Traction Lug,
 stability is enhanced, traction is
 increased by 25% and the contact
 area is improved by 50%


PU - RUBBER

SOLE 72

EN ISO 20345:2022+A1:2024

BASIC
 CERAMIC WITH
 NALS

SLIP RESISTANCE	
FORWARD HEEL SLIP	0,51
BACKWARD FOREPART SLIP	0,52

SR
 CERAMIC WITH
 GLYCERINE

SLIP RESISTANCE	
FORWARD HEEL SLIP	0,32
BACKWARD FOREPART SLIP	0,33