



EN ISO 20345:2022



DIVENTURE

GARDENA
70538-05L
S3S FO *CI SC LG SR
Size: 36-48

Weight: 740 gr.

Fit: 11

Working Environment:

 Building, Wood-metal carpentry,
 Oil industry, Farming and
 Gardening


FEATURES

UPPER

 Greased Nubuk Leather Hydro
 1,8-2,0 mm
 Greased Nubuk Leather Hydro
 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY CCYCLED® SR

 Two-component PU sole made
 from recycled Ccycled® material
 with additional LG and SC
 requirements and SR
 characteristics.

TECHNOLOGIES

Removable Insole


 Anatomical breathable insole.
 Resistant fabric with recycled open-
 cell foam that absorbs shocks and
 reduces fatigue. Eliminates sweat
 with its high ability to evaporate it.
 Continuous comfort for months and
 months of use


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Recycled non
 metal perforation resistant insert to
 over 1100 N with a 3.0 mm truncated
 cone nail. Protection over the entire
 sole of the foot. Flexible and
 comfortable


Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.

Torsional stability


STABIL•ACTIVE

 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


 PROGRESSIVE CUSHIONING
 AND ADAPTIVE STABILITY

 D3O materials are made using a
 combination of advanced polymer
 chemistry and cutting-edge science.
 It absorbs and dissipates energy
 during and impact, with superior
 stability, cushioning and anti-fatigue
 effect.


PU - PU

SOLE 70

SLIP RESISTANCE

EN ISO 20345:2022

BASIC
 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,39
BACKWARD FOREPART SLIP ≥ 0.36	0,42

SR
 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20
BACKWARD FOREPART SLIP ≥ 0.22	0,31