



EN ISO 20345:2022+A1:2024



DIVENTURE

LATEMAR BOA®

71565-00L

S7S FO HI HRO CI CR SC LG SR

Size: 36-48

Weight: 920 gr.

Fit: 11

Working Environment:

Cold places, Farming and Gardening, Mountains, Building



FEATURES

UPPER

MicroFiber Nabuk 1,8-2,0 mm
No ladder H.T. Fabric
Reflex insert

LINING

GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Half-knee Boot

SOLE

PU-VIBRAM® ARCTIC GRIP

PU midsole with scuff cap (SC) made with recycled Cycled material. VIBRAM rubber outsole with Arctic Grip Pro inserts and "Minus 40" compound. SR and Ladder Grip standard.

Boa® lace length

L+1 - 120cm

TECHNOLOGIES


Removable Insole



The ideal insole in recycled material for footwear with "CI" cold protection. The presence of felt with an "aluminized" film for bottom insulation keeps the foot dry and warm.



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamicHC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Diventure Arktic has successfully passed the Ice Grip Index (Gi) (kN) test in accordance with Swedish standard SS 657177:2024 - Ice Grip Performance Footwear - Swedish Institute for Standards.



PU - RUBBER

SOLE 71

EN ISO 20345:2022+A1:2024

BASIC CERAMIC WITH NALS

SLIP RESISTANCE	EN ISO 20345:2022+A1:2024
FORWARD HEEL SLIP ≥ 0.31	0,52
BACKWARD FOREPART SLIP ≥ 0.36	0,54

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20
BACKWARD FOREPART SLIP ≥ 0.22	0,29