



EN ISO 20345:2022



DIVENTURE

MARMOLADA ZIP
70550-00L
S3S FO *CI SC LG SR
Size: 36-48
Weight: 810 gr.

Fit: 11

Working Environment:

 Building, Wood-metal carpentry,
 Oil industry, Farming and
 Gardening


FEATURES

TOMAIA

 Greased Nubuk Leather Hydro
 1,8-2,0 mm
 Reflex insert

FODERA

3D Green Air 320 gr.

FOD. ANTISCIVOLO

DUALMICRO

SUOLETTA

QRS02 Green

PUNTALE

Fiber cap SXT

RESISTENZA ALLA PERFORAZIONE

KX Antiperforation recycled PS

TIPOLOGIA

Ankle boot

SUOLA

PU DUAL-DENSITY CCYCLED® SR

Two-component PU sole made from recycled Ccycled® material with additional LG and SC requirements and SR characteristics.

TECNOLOGIE

Suoletta Intercambiabile

QRS02
GREEN

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Elementi di Protezione


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Stabilità Trasversale

dynamicControl
 technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Stabilità Torsione


STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Caratteristiche Elettriche



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Altro


PROGRESSIVE CUSHIONING AND ADAPTIVE STABILITY

D3O materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.



PU - PU

SOLE 70

SLIP RESISTANCE

EN ISO 20345:2022

BASIC
 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,39
BACKWARD FOREPART SLIP ≥ 0.36	0,42

SR
 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,20
BACKWARD FOREPART SLIP ≥ 0.22	0,31