



EN ISO 20345:2022+A1:2024



DIVENTURE

PORDOI

72564-00L

S3S FO HI HRO *CI CR SC LG SR
Size: 36-48

Weight: 980 gr.

Fit: 11

Working Environment:

Building, Wood-metal carpentry,
Engineering, Farming and
Gardening


FEATURES

UPPER

Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Full Grain Leather Hydro
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Half-knee Boot

SOLE

**PU-VIBRAM® RECYCLED ECOSTEP
- TRACTION LUG**

PU midsole with scuff cap (SC)
made with recycled Cycled
material. VIBRAM rubber outsole
with Traction Lug technology and
"Ecostep Pro" compound. SR and
Ladder Grip standard.

TECHNOLOGIES

Removable Insole

QRS02 ^{GREEN}

Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use


Protection elements

KX ^{GREEN} **RESISTANT
TO 3.0 mm.
NAILS** **fibercap sxt**

Composite toecap with fiberglass.
Resistant to over 200J. Recycled non
metal perforation resistant insert to
over 1100 N with a 3.0 mm truncated
cone nail. Protection over the entire
sole of the foot. Flexible and
comfortable


Lateral stability

dynamicControl
technology

Ergonomic rigid structure. It
accommodates the heel, adjusting the
foot support and control of the ankle
in sideways movements. The plastic
material increases protection of the
ankle against sharp or pointy objects.


Torsional stability

STABIL•ACTIVE

Support made of rigid plastic
material. It supports the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.


Electrical features


ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other


TRACTION LUG

It is the ideal solution for those
working on uneven, rocky and
abrasive terrain. With Traction Lug,
stability is enhanced, traction is
increased by 25% and the contact
area is improved by 50%


PU - RUBBER

SOLE 72

EN ISO 20345:2022+A1:2024

BASIC
CERAMIC WITH
NALS

SLIP RESISTANCE		
FORWARD HEEL SLIP ≥ 0.31	0,51	
BACKWARD FOREPART SLIP ≥ 0.36	0,52	

SR
CERAMIC WITH
GLYCERINE

SLIP RESISTANCE		
FORWARD HEEL SLIP ≥ 0.19	0,32	
BACKWARD FOREPART SLIP ≥ 0.22	0,33	