



EN ISO 20345:2022+A1:2024



DIVENTURE
PORDOI
72564-04L

S7S FO HI HRO *CI CR SC LG SR

Size: 36-48
Weight: 980 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Wood-metal
carpentry



FEATURES

UPPER

Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Full Grain leather Hydro
Reflex insert

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Half-knee Boot

SOLE

PU-VIBRAM® RECYCLED ECOSTEP® - TRACTION LUG

PU midsole with scuff cap (SC) made with recycled Cycled material. VIBRAM rubber outsole with Traction Lug technology and "Ecostep Pro" compound. SR and Ladder Grip standard.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Recycled non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic **HC** control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other



It is the ideal solution for those working on uneven, rocky and abrasive terrain. With Traction Lug, stability is enhanced, traction is increased by 25% and the contact area is improved by 50%



PU - RUBBER

SOLE 72

EN ISO 20345:2022+A1:2024

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP	≥ 0.31	0,51
BACKWARD FOREPART SLIP	≥ 0.36	0,52

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP	≥ 0.19	0,32
BACKWARD FOREPART SLIP	≥ 0.22	0,33