



EN ISO 20345:2011 

ENDURANCE
ANDALO
81017-00L

S3 *CI SRC

Size: 36-48
Weight: 670 gr.

Fit: 11

Working Environment:
 Building, Wood-metal carpentry,
 Farming and Gardening,
 Multipurpose





FEATURES

- UPPER**
 Grain leather Hydro 1,8-2,0 mm
 Greased Nubuk Dakar Leather
 Hydro 1,8-2,0 mm
 Fabric of High Tenacity
- LINING**
 3D Air circulation 320 gr.
- ANTISLIP LINING**
 DUALMICRO
- INSOLE**
 Climaction-Fit 337
- TOE CAP**
 Fiber cap SXT
- RESISTANCE TO PERFORATION**
 Textile resistant to 3.0 mm nail
- TYPE**
 Low Shoe

SOLE
PU DUAL-DENSITY SRC
 Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)

		SOLE 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE °) ≥ 0.28	0.52
		0.48
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE °) ≥ 0.13	0.23
		0.18

EN ISO 20344:2011


TECHNOLOGIES

Removable Insole **337**
climaction fit


Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements

 **RESISTANT TO 3.0 mm. NAILS** **fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.




Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.