



EN ISO 20345:2011



ENDURANCE  
**ARKO BOA®**  
81184-03L

**S3 \*CI SRC**

**Size:** 36-48  
**Weight:** 680 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Farming and Gardening,  
Multipurpose



## FEATURES

### UPPER

Grain leather Hydro 1,8-2,0 mm  
No ladder H.T. Fabric  
Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Climaction-Fit 337

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**337**  
**climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Protection elements

**RESISTANT TO 3.0 mm NAILS** **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



**FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



## SRC (SRA+SRB)



|   |  | SOLE 81<br>PU - PU |
|---|--|--------------------|
| <b>SRA</b><br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32<br>HEEL<br>(CONTACT ANGLE 1°)<br>≥0.28 | <b>0.52</b>        |
| <b>SRB</b><br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18<br>HEEL<br>(CONTACT ANGLE 1°)<br>≥0.13 | <b>0.23</b>        |
|   |  | <b>0.18</b>        |

EN ISO 20344:2011