sixton SAFETY SHOES peak

12/10/2024

EN ISO 20345:2011

ENDURANCE

CORVARA

81087-05L

S3 *CI SRC

Size: 36-48
Weight: 710 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry, Farming and Gardening, Multipurpose

FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro 1,8-2,0 mm
Full Grain leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Climaction-Fit 337

TOE CAP
Fiber cap SXT

RESISTANCE TO PERFORATION
KX Antiperforation PS

TYPE
Ankle boot

SOLE
PU DUAL-DENSITY SRC
Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

S E FO A WRU P SRC CI AVAILABLE

SRC (SRA+SRB)

		SOLE 81 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.52
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.48
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.23
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.18

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

climaction 337 fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort .

Protection elements

KX RESISTANT TO 3.0 mm. NAILS

fibercap sxt

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic Control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale