



EN ISO 20345:2011


 ENDURANCE  
**LABRADOR**  
 81152-01L

**S1P SRC**
**Size:** 36-48  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**  
 Building, Wood-metal carpentry,  
 Farming and Gardening,  
 Multipurpose


## FEATURES

### TOMAIA

Drummed Suede Leather 1,8-2,0 mm  
 Fabric of High Tenacity  
 Drummed Suede Leather Hydro  
 1,6-1,8 mm

### FODERA

3D Air circulation 320 gr.

### FOD. ANTISCIVOLO

DUALMICRO

### SUOLETTA

Climaction-Fit 337

### PUNTALE

Fiber cap SXT

### RESISTENZA ALLA PERFORAZIONE

KX Antiperforation PS

### TIPOLOGIA

Ankle boot

### SUOLA

#### PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

## TECNOLOGIE

### Suoletta Intercambiabile

337

**climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



### Elementi di Protezione



RESISTANT TO 3.0 mm. NAILS

**fibercap sxt**

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Stabilità Trasversale

**dynamic HC control technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Stabilità Torsione

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




### Caratteristiche Elettriche

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Altro

**DUALMICRO DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



## SRC (SRA+SRB)

	SOLE 81 PU - PU	
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.52</b> <b>0.48</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.23</b> <b>0.18</b>

EN ISO 20344:2011