



EN ISO 20344:2011



ENDURANCE
MONTANA

81156-07L

S3 CI SRC

Size: 36-48
Weight: 750 gr.

Fit: 11

Working Environment:
Building, Farming and Gardening,
Mountains, Cold places



FEATURES

UPPER

Full Grain-Anilina Leather-Hydro
1,8-2,0 mm

LINING

Soft Full Grain Leather
GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Half-knee Boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

TECHNOLOGIES


Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



SOLE 81
PU - PU

TEST	FLAT (CONTACT ANGLE °)	HEEL (CONTACT ANGLE °)	SCORE
SRA CERAMIC + DETERGENT SOLUTION	≥0.32	≥0.28	0.52
SRB STEEL + GLYCEROL	≥0.18	≥0.13	0.23

EN ISO 20344:2011