



EN ISO 20344:2011



ENDURANCE  
**MONTANA**

**81156-23L**

**S3 WR CI SRC**

**Size:** 36-48  
**Weight:** 850 gr.

**Fit:** 11

**Working Environment:**  
Building, Farming and Gardening,  
Mountains, Cold places



**FEATURES**

**UPPER**

Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm

**LINING**

Soft Full Grain Leather  
GenuineWool Polar

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Dual insulation

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

KX Antiperforation PS

**TYPE**

Half-knee Boot

**SOLE**

**PU DUAL-DENSITY SRC**

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

**TECHNOLOGIES**


**Removable Insole**



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



**Protection elements**



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



SOLE B1  
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.23
		0.18

EN ISO 20344:2011