



EN ISO 20345:2011



ENDURANCE

ROTOR BOA®
81375-00L
S3 CI SRC
Size: 36-48

Weight: 800 gr.

Fit: 11

Working Environment:

 Building, Wood-metal carpentry,
 Mountains, Cold places


FEATURES

UPPER

 Grain leather Hydro 1,8-2,0 mm
 Reflex insert

LINING

 3D Air circulation 320 gr.
 GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamicHC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability


STABIL-ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other


**FIT TO GO
 FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



SRC (SRA+SRB)


 SOLE 81
 PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.23
		0.18

EN ISO 20344:2011