



EN ISO 20344:2011



ENDURANCE  
**STEPPA**  
81001-01L

**S3 \*CI SRC**

**Size:** 36-48  
**Weight:** 710 gr.

**Fit:** 11

**Working Environment:**  
Multipurpose, Building, Wood-metal carpentry, Farming and Gardening



**FEATURES**

**UPPER**

Greased Nubuk Leather Hydro  
1,8-2,0 mm  
Fabric of High Tenacity

**LINING**

3D Air circulation 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Climaction-Fit 337

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

Textile resistant to 3.0 mm nail

**TYPE**

Ankle boot

**SOLE**

**PU DUAL-DENSITY SRC**

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

**TECHNOLOGIES**

**Removable Insole**

**337 climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



**Protection elements**

**RESISTANT TO 3.0 mm. NAILS** *fibercap sxt*

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**

**dynamic control technology**

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



**Torsional stability**

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**

**WED**

Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**

**DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



	SOLE B1 PU - PU	
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.52</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.23</b>

EN ISO 20344:2011