



EN ISO 20345:2011



EXCURSION

**ALLEGHE**  
 31450-02L

**S3 \*CI WR SRC**
**Size:** 36-50  
**Weight:** 740 gr.

**Fit:** 11

**Working Environment:**

 Building, Wood-metal carpentry,  
 Farming and Gardening,  
 Mountains


## FEATURES

### UPPER

 MicroFiber Suede 1,8-2,0 mm  
 No ladder H.T. Fabric  
 MicroFiber TOP 1,8-2,0 mm  
 Reflex insert

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

Qrs01

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY SRC

PU foam insole, light and comfortable. Modular overtone to protect uppers. Designed also for indoor use, self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.

## TECHNOLOGIES

### Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



### Protection elements


 RESISTANT  
 TO 3.0 mm.  
 NAILS

**alu-sxt2.0**  
 aluminum

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

**dynamic HC control**  
 technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability


**STABIL • ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



+WATERPROOF UPPER

The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.



## SRC (SRA+SRB)


 SOLE 31  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT $\geq 0.32$	<b>0.46</b>
	HEEL (CONTACT ANGLE 7°) $\geq 0.28$	<b>0.41</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT $\geq 0.18$	<b>0.22</b>
	HEEL (CONTACT ANGLE 7°) $\geq 0.13$	<b>0.21</b>

EN ISO 20344:2011