



EN ISO 20344:2011



EXCURSION
FIEMME
31471-00L

S3 SRC *CI AVAILABLE

Size: 36-50
Weight: 650 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Mountains



FEATURES

TOMAIA

MicroFiber Suede 1,8-2,0 mm
No ladder H.T. Fabric
MicroFiber TOP 1,8-2,0 mm
Reflex insert

FODERA

3D Air circulation 320 gr.

**FOD. ANTISCIVOLO
DUALMICRO**

**SUOLETTA
Qrs01**

PUNTALE

Alu SXT 2.0 Toe cap

**RESISTENZA ALLA
PERFORAZIONE**

KX Antiperforation PS

TIPOLOGIA

Low Shoe

SUOLA

PU DUAL-DENSITY SRC

PU foam insole, light and comfortable. Modular overtoe to protect uppers. Designed also for indoor use, self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.

TECNOLOGIE

Suoletta Intercambiabile



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



SRC (SRA+SRB)



		SOLE 31 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.46
	HEEL (CONTACT ANGLE °) ≥0.28	0.41
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.22
	HEEL (CONTACT ANGLE °) ≥0.13	0.21

EN ISO 20344:2011