sixton SAFETY SHOES peak

EN ISO 20345:2011

EXCURSION

FIEMME

31471-00L

S3 SRC *CI AVAILABLE

Size: 36-50
Weight: 650 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry, Farming and Gardening, Mountains

FEATURES

UPPER
MicroFiber Suede 1,8-2,0 mm
No ladder H.T. Fabric
MicroFiber TOP 1,8-2,0 mm
Reflex insert

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Qrs01

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail

TYPE
Low Shoe

SOLE
PU DUAL-DENSITY SRC
PU foam insole, light and comfortable. Modular overtoe to protect uppers. Designed also for indoor use, self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.

S E FO A WRU P CI SRC

SRC (SRA+SRB)

SOLE 31
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.46
	HEEL (CONTACT ANGLE 7°) ≥0.28	0.41
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.22
	HEEL (CONTACT ANGLE 7°) ≥0.13	0.21

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

QRS01

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

Protection elements

KX RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale