



EN ISO 20345:2011 

EXCURSION
LAVAREDO
31407-03L

S3 CI SRC

Size: 36-50
Weight: 730 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Engineering, Multipurpose



FEATURES

- UPPER**
MicroFiber Suede 1,8-2,0 mm
No ladder H.T. Fabric
MicroFiber TOP 1,8-2,0 mm
Soft Full Grain Leather Hydro
Reflex insert
No ladder H.T. Fabric
- LINING**
3D Air circulation 320 gr.
GenuineWool Polar
- ANTISLIP LINING**
DUALMICRO
- INSOLE**
Dual insulation
- TOE CAP**
Alu SXT 2.0 Toe cap
- RESISTANCE TO PERFORATION**
KX Antiperforation PS
- SOLE**
PU DUAL-DENSITY SRC
PU foam insole, light and comfortable. Modular overtoe to protect uppers. Designed also for indoor use, self-cleaning reliefs. Extra-grip PU tread with SRC slip-resistant performance.
- TYPE**
Half-knee Boot



TECHNOLOGIES

Removable Insole

DUAL INSULATION

Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



Protection elements

KX RESISTANT TO 3.0 mm. NAILS **alu-sxt2.0 aluminium**

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.





Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




SRC (SRA+SRB)

		SOLE 31 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32 HEEL (CONTACT ANGLE °) ≥ 0.28	0.46
SRB STEEL + GLYCEROL	FLAT ≥ 0.18 HEEL (CONTACT ANGLE °) ≥ 0.13	0.22
EN ISO 20344:2011		

Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.