



EN ISO 20345:2022



EXCURSION
SESTRIERE
31498-06L

S3S FO *CI SC SR

Size: 36-48
Weight: 730 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Mountains



FEATURES

UPPER

MicroFiber TOP 1,8-2,0 mm
MicroFiber Suede 1,8-2,0 mm
Reflex insert
PERSPAIR HYPERTEX with
diversified areas with high
abrasion resistance

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Ankle boot

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use



Protection elements



Toecap "Alu Sxt 2.0" with
differentiated thicknesses, resistant
to 200J. Non metal perforation
resistant Insert to over 1100 N with a
3.0 mm truncated cone nail. Protection
over the entire sole of the foot.
Flexible and comfortable



Lateral stability



Ergonomic rigid structure. It
accommodates the heel, adjusting the
foot support and control of the ankle
in sideways movements. The plastic
material increases protection of the
ankle against sharp or pointy objects.



Torsional stability



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other




Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



PU - PU
SOLE 31

SLIP RESISTANCE
EN ISO 20344:2021

	FORWARD HEEL SLIP	BACKWARD FOREPART SLIP	AVAILABLE
BASIC CERAMIC WITH NALS	0,33 ≥ 0.31	0,42 ≥ 0.36	
SR CERAMIC WITH GLYCERINE	0,21 ≥ 0.19	0,26 ≥ 0.22	