



EN ISO 20345:2022



EXCURSION
SESTRIERE BOA
31520-00L

S3S FO *CI SC SR

Size: 36-48
Weight: 730 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Mountains



FEATURES

TOMAIA

MicroFiber TOP 1,8-2,0 mm
MicroFiber Suede 1,8-2,0 mm
Reflex insert
PERSPAIR HYPERTEX with
diversified areas with high
abrasion resistance

FODERA

3D Green Air 320 gr.

FOD. ANTISCIVOLO

DUALMICRO

SUOLETTA

QRS02 Green

PUNTALE

Alu SXT 2.0 Toe cap

**RESISTENZA ALLA
PERFORAZIONE**

KX Antiperforation PS

TIPOLOGIA

Ankle boot

SUOLA

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.

Lunghezza filo Boa®

M4 - 120cm

TECNOLOGIE

Suoletta Intercambiabile



Anatomical breathable insole.
Resistant fabric with recycled open-
cell foam that absorbs shocks and
reduces fatigue. Eliminates sweat
with its high ability to evaporate it.
Continuous comfort for months and
months of use



Elementi di Protezione



Toe cap "Alu Sxt 2.0" with
differentiated thicknesses, resistant
to 200J. Non metal perforation
resistant Insert to over 1100 N with a
3.0 mm truncated cone nail. Protection
over the entire sole of the foot.
Flexible and comfortable



Stabilità Trasversale



Ergonomic rigid structure. It
accommodates the heel, adjusting the
foot support and control of the ankle
in sideways movements. The plastic
material increases protection of the
ankle against sharp or pointy objects.



Stabilità Torsione



Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Caratteristiche Elettriche










ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Altro



Double non-slip layer of microfibre,
resistant up to 200,000 cycles. Makes
the footwear more comfortable,
blocking the foot during use.



PU - PU		SOLE 31		SLIP RESISTANCE	
				EN ISO 20344:2021	
BASIC CERAMIC WITH NALS	FORWARD HEEL SLIP ≥ 0.31	0,33			
	BACKWARD FOREPART SLIP ≥ 0.36	0,42			
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,21			
	BACKWARD FOREPART SLIP ≥ 0.22	0,26	