



EN ISO 20345:2022



EXCURSION

**SESTRIERE BOA**  
**31520-00L**
**S3S FO \*CI SC SR**
**Size:** 36-48  
**Weight:** 730 gr.

**Fit:** 11

**Working Environment:**

Building, Wood-metal carpentry,  
Farming and Gardening,  
Mountains


## FEATURES

### UPPER

MicroFiber TOP 1,8-2,0 mm  
MicroFiber Suede 1,8-2,0 mm  
Reflex insert  
PERSPAIR HYPERTEX with  
diversified areas with high  
abrasion resistance

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

QRS02 Green

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and  
in-between sole with ESD  
compound. For use in contact with  
sensitive electronic equipment.  
Light and comfortable, very  
versatile, highly non-slip SRC  
Antislip standard.

**Boa® lace length**  
M4 - 120cm

## TECHNOLOGIES

### Removable Insole

**QRS02** GREEN

Anatomical breathable insole.  
Resistant fabric with recycled open-  
cell foam that absorbs shocks and  
reduces fatigue. Eliminates sweat  
with its high ability to evaporate it.  
Continuous comfort for months and  
months of use


### Protection elements


**RESISTANT**  
**TO 3.0 mm.**  
**NAILS**
**alu-sxt2.0**  
aluminium

Toecap "Alu Sxt 2.0" with  
differentiated thicknesses, resistant  
to 200J. Non metal perforation  
resistant Insert to over 1100 N with a  
3.0 mm truncated cone nail. Protection  
over the entire sole of the foot.  
Flexible and comfortable


### Lateral stability

**dynamicControl**  
technology

Ergonomic rigid structure. It  
accommodates the heel, adjusting the  
foot support and control of the ankle  
in sideways movements. The plastic  
material increases protection of the  
ankle against sharp or pointy objects.


### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.


### Electrical features


ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

### Other

**DUALMICRO**  
**DUALMICRO**

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.




### PU - PU

SOLE 31

### SLIP RESISTANCE

EN ISO 20344:2021

**BASIC**  
CERAMIC WITH  
NALS

FORWARD HEEL SLIP ≥ 0.31	0,33	
BACKWARD FOREPART SLIP ≥ 0.36	0,42	

**SR**  
CERAMIC WITH  
GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,21	
BACKWARD FOREPART SLIP ≥ 0.22	0,26	