




**EN ISO 20345:2022** 


**EXCURSION**  
**SUSA BOA**  
**31521-00L**

**S3S FO \*CI SC SR**

**Size:** 36-48  
**Weight:** 650 gr.

**Fit:** 11

**Working Environment:**  
 Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Farming and Gardening



**FEATURES**

**UPPER**  
 MicroFiber TOP 1,8-2,0 mm  
 Reflex insert  
 MicroFiber Suede 1,6-1,8 mm  
 PERSPAIR HYPERTEX with diversified areas with high abrasion resistance

**SOLE**  
**PU / PU ESD-PLUS SRC**  
 Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

**LINING**  
 3D Green Air 320 gr.

**ANTISLIP LINING**  
 DUALMICRO

**INSOLE**  
 QRS02 Green

**TOE CAP**  
 Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**  
 KX Antiperforation PS


**TYPE**  
 Low Shoe



**TECHNOLOGIES**

**Removable Insole**  
**QRS02 GREEN**

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



**Protection elements**

**KX RESISTANT TO 3.0 mm. NAILS** **alu-sxt2.0 aluminium**

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**  
**dynamicControl technology**



Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.




**Torsional stability**  
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



PU - PU SOLE 31		SLIP RESISTANCE EN ISO 20344:2021	
<b>BASIC</b> CERAMIC WITH NALS	FORWARD HEEL SLIP $\geq 0.31$	<b>0,33</b>	
	BACKWARD FOREPART SLIP $\geq 0.36$	<b>0,42</b>	
<b>SR</b> CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP $\geq 0.19$	<b>0,21</b>	
	BACKWARD FOREPART SLIP $\geq 0.22$	<b>0,26</b>	

**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**  
**DUALMICRO DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.