sixton SAFETY SHOES peak

EN ISO 20345:2022

EXCURSION

SUSA BOA

31521-00L

S3S FO *CI SC SR

Size: 36-48
Weight: 650 gr.

Fit: 11

Working Environment:
Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Farming and Gardening

FEATURES

UPPER
MicroFiber TOP 1,8-2,0 mm
Reflex insert
MicroFiber Suede 1,6-1,8 mm
PERSPAIR HYPERTEX with diversified areas with high abrasion resistance

LINING
3D Green Air 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
QRS02 Green

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
Textile resistant to 3.0 mm nail

TYPE
Low Shoe

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

Boa® lace length
L6 - 85cm



TECHNOLOGIES

Removable Insole

QRS02 GREEN

Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

Protection elements

RESISTANT TO 3.0 mm. NAILS

alu-sxt 2.0 aluminium

Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability

dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

Electrical features

ESD

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

Maspica Srl a Socio Unico Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale