



EN ISO 20345:2022



EXCURSION

SUSA
31499-03L
S3S FO *CI SC SR
Size: 36-48

Weight: 650 gr.

Fit: 11

Working Environment:

Multipurpose, Wood-metal carpentry, Farming and Gardening, Logistics and Light Industry



FEATURES

UPPER

MicroFiber TOP 1,8-2,0 mm
Reflex insert
PERSPAIR HYPERTEX with diversified areas with high abrasion resistance

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Elementi di Protezione



RESISTANT TO 3.0 mm. NAILS



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Stabilità Trasversale

dynamicControl
technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Stabilità Torsione

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Caratteristiche Elettriche



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Altro

DUALMICRO
DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



PU - PU

SOLE 31

SLIP RESISTANCE

EN ISO 20344:2021

BASIC

CERAMIC WITH NAILS

FORWARD HEEL SLIP ≥ 0.31 **0,33**

BACKWARD FOREPART SLIP ≥ 0.36 **0,42**



SR

CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19 **0,21**

BACKWARD FOREPART SLIP ≥ 0.22 **0,26**

