



EN ISO 20345:2022



GREENBALL TACKEBACK BOA®

60558-00L
S3S FO HI *CI HRO SR
Size: 38-48
Weight: 615 gr.

Fit: 11

Working Environment:
 Multipurpose, Finishing-off
 building, Components and
 Automotive, ESD Areas


FEATURES

UPPER

 Micropell KARVIN sp. 1,8-2,0 mm.
 nero IDROPELLENTE
 No ladder, recycled Knit textile

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Nano Toe SXT

RESISTANCE TO PERFORATION

KK7 Antiperforation recycled PS

TYPE

Low Shoe

SOLE

**PU-D30-VIBRAM® RECYCLED
ECOSTEP**

 PU midsole with recycled Cycled®
 material and ESD features.
 RUBBER OUTSOLE ECOSTEP PRO
 BY VIBRAM. High slip resistance.
 Standard Antislip SR.

Boa® lace length

Li2 - 55cm

TECHNOLOGIES

Removable Insole


 Anatomical breathable insole.
 Resistant fabric with recycled open-
 cell foam that absorbs shocks and
 reduces fatigue. Eliminates sweat
 with its high ability to evaporate it.
 Continuous comfort for months and
 months of use


Protection elements


 Composite toe cap, reinforced with
 carbon nanotubes. Resistant > 200J
 Non metal perforation resistant insert
 to over 1100 N with a 3.0 mm
 truncated cone nail. Protection over
 the entire sole of the foot. Flexible
 and comfortable.


Lateral stability

dynamic HC control
technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE


 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


**FIT TO GO
FURTHER™**

 A patented closing system with a multi
 coated stainless steel cable. The
 BOA® Fit System delivers micro-
 adjustable precision fit, engineered to
 perform in the toughest conditions.


PU - RUBBER

SOLE 60


SLIP RESISTANCE

EN ISO 20344:2021

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP ≥ 0.31	0,31	
BACKWARD FOREPART SLIP ≥ 0.36	0,36	

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,19	
BACKWARD FOREPART SLIP ≥ 0.22	0,22	