



EN ISO 20345:2022


 HELEVO
NEON BOA®
66532-01L
S3S FO SR
Size: 35-48
Weight: 500 gr.

Fit: 11

Working Environment:
 Multipurpose, Logistics and Light
 Industry, Components and
 Automotive, ESD Areas


FEATURES

UPPER

 MicroFiber Suede 1,6-1,8 mm
 Recycled Digitex Hydro

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

TALENT FIT D3O

TOE CAP

Nano Toe SXT

RESISTANCE TO PERFORATION

KK7 Antiperforation recycled PS

TYPE

Low Shoe

SOLE

PU DUAL-DENSITY CCYCLED® SR

 Two-components PU sole, Outer-
 and in-between sole with ESD
 compound. With recycled material
 Ccycled®, highly non-slip SR
 Antislip standard.

Boa® lace length
 L6 - 65cm

TECHNOLOGIES

Removable Insole


 Breathable anatomic insole. Durable
 recycled fabric with open cell foam.
 Absorbs shocks and decreases
 fatigue. Eliminates sweat with its high
 ability to evaporate it. Continuous
 comfort for months and months of
 use.


Protection elements


 Composite toe cap, reinforced with
 carbon nanotubes. Resistant > 200J
 Non metal perforation resistant insert
 to over 1100 N with a 3.0 mm
 truncated cone nail. Protection over
 the entire sole of the foot. Flexible
 and comfortable.


Lateral stability

dynamic HC control
technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability

STABIL•ACTIVE

 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


**FIT TO GO
 FURTHER™**

 A patented closing system with a multi
 coated stainless steel cable. The
 BOA® Fit System delivers micro-
 adjustable precision fit, engineered to
 perform in the toughest conditions.


PU - PU

SOLE 66

SLIP RESISTANCE

EN ISO 20345:2022

BASIC

 CERAMIC WITH
 NALS

FORWARD HEEL SLIP ≥ 0.31	0,47	
BACKWARD FOREPART SLIP ≥ 0.36	0,51	

SR

 CERAMIC WITH
 GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	0,36	
BACKWARD FOREPART SLIP ≥ 0.22	0,35	