



EN ISO 20344:2011


**HORIZON  
CUPRA**
**53071-16**
**S1 SRC**
**Size:** 36-48  
**Weight:** 610 gr.

**Fit:** 10,5

**Working Environment:**  
 Logistics and Light Industry,  
 Farming and Gardening,  
 Multipurpose

**FEATURES**
**UPPER**

Drummed leather Hydro 1,8-2,0 mm

**LINING**

3D Air circulation 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Flyfit

**TOE CAP**

Steel Toe Cap

**TYPE**

Low Shoe

**SOLE**
**PU DUAL-DENSITY SRC**

Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

**TECHNOLOGIES**
**Removable Insole**


The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

**Protection elements**
**STEEL TOECAP**

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber.


**SRC (SRA+SRB)**

 SOLE 52 - 53  
**PU - PU**

|                                                     |                                    |             |
|-----------------------------------------------------|------------------------------------|-------------|
| <b>SRA</b><br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32                      | <b>0.36</b> |
|                                                     | HEEL<br>(CONTACT ANGLE °)<br>≥0.28 |             |
| <b>SRB</b><br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18                      | <b>0.19</b> |
|                                                     | HEEL<br>(CONTACT ANGLE °)<br>≥0.13 |             |

EN ISO 20344:2011

**Lateral stability**
**dynamic HC control  
technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.


**Torsional stability**
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.


**Electrical features**


Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.


**Other**
**DUALMICRO  
DUALMICRO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.