



EN ISO 20345:2011


 HORIZON  
**CUPRA**  
 53071-17L

**S3 SRC**
**Size:** 36-48  
**Weight:** 630 gr.

**Fit:** 10,5

**Working Environment:**  
 Logistics and Light Industry,  
 Farming and Gardening, Wood-  
 metal carpentry, Multipurpose

## FEATURES

### UPPER

Drummed leather Hydro 1,8-2,0 mm

### LINING

3D Air circulation 320 gr.

### INSOLE

Flyfit

### TOE CAP

Steel Toe Cap

### RESISTANCE TO PERFORATION

Steel Plate

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY SRC

Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

## TECHNOLOGIES

### Removable Insole


**FLYFIT**

The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.



### Protection elements

#### STEEL PROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.



## SRC (SRA+SRB)


 SOLE 52 - 53  
 PU - PU

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.36</b> <b>0.42</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.19</b> <b>0.14</b>

EN ISO 20344:2011

### Lateral stability

**dynamic HC control**  
 technology


Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.




### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other

**DUAL MICRO DWT WICKO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.