





EN ISO 20345:2011



HORIZON

CUPRA

53071-17L

S3 SRC

Size: 36-48 Weight: 630 gr.

Fit: 10,5

Working Environment:

Logistics and Light Industry, Farming and Gardening, Woodmetal carpentry, Multipurpose

FEATURES

UPPER

Drummed leather Hydro 1,8-2,0

LINING

3D Air circulation 320 gr.

INSOLE

Flvfit

TOE CAP

Steel Toe Cap

RESISTANCE TO PERFORATION

SRC (SRA+SRB)

≥0.32

HEEL (CONTACT ANGLE 7°) ≥0.28

≥0.18

NIALTANGLE ≥0.13

SOLE 52 - 53 **PU - PU**

0.36

0.42

0.19

0.14

20344:201

Steel Plate

TYPE

Low Shoe

SRA

DETERGENT SOLUTION

SRB GLYCFROL

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with selfcleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

TECHNOLOGIES

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A selfforming antibacterial foam layer ensures comfort and correct support of the foot.

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

paint.

Protection elements



STEEL PROTECTION

Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant

Steel toecap, with anti-corrosion

paint. Protection of over 200J.

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

