



EN ISO 20345:2011



HORIZON  
**GAMMA**

52421-01L

S3 \*CI SRC

**Size:** 36-48  
**Weight:** 760 gr.

**Fit:** 10,5

**Working Environment:**  
Building, Wood-metal carpentry,  
Farming and Gardening,  
Engineering



**FEATURES**

**UPPER**  
Greased Nubuk Dakar Leather  
Hydro 1,8-2,0 mm  
Reflex insert

**LINING**  
Soft Full Grain Leather Hydro  
Double non-slip layer of  
microfibre, resistant up to 200,000  
cycles. Makes the footwear more  
comfortable, blocking the foot  
during use.

**INSOLE**  
Climaction-Fit 337

**TOE CAP**  
Steel Toe Cap

**RESISTANCE TO PERFORATION**  
Steel Plate

**TYPE**  
Ankle boot

**SOLE**  
**PU DUAL-DENSITY SRC**  
Two-component PU sole with self-  
cleaning pattern, extremely flexible  
for various places of use, both  
indoor and outdoor, with SRC  
Antislip Standard.

**TECHNOLOGIES**

**Removable Insole**  
**337**  
**climaction fit**

Removable anatomic and ergonomic  
insole. Absorbent and transpiring  
open-cell foam support. Keeps feet  
fresh. Specifically-designed  
thermoforming for exceptional  
comfort.



**Protection elements**  
**STEEL PROTECTION**

Steel toecap, with anti-corrosion  
paint. Protection of over 200J.  
Comfortable fit. Stainless steel Plate  
resistant puncture with acid-resistant  
paint.




**Lateral stability**  
**dynamic HC control**  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



**Torsional stability**  
**STABIL ACTIVE**

It supports the heel bone, the instep  
and tarsal joints, without altering  
energy absorption. A support for the  
natural movement of the foot; it  
provides comfort and greater  
stability.



**Electrical features**  
**WED**  
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



**Other**  
**DUAL MICRO DWT WICBO**

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



**SRC (SRA+SRB)**

SOLE 52 - 53 PU - PU		
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.36</b> <b>0.42</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b> <b>0.14</b>

EN ISO 20344:2011